Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2311	(updat$3 modify$3 chang$3) same (column$1) same database	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:18
L2	322	(updat$3 modify$3 chang$3) with (column$1 field$1) with application same database$1	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:25
L3	103	(updat$3 modify$3 chang$3) with (column$1 field$1) with application same database$1 and @rlad<="20020111"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:26
L4	52	(updat$3 modify$3 chang$3) with (column$1 field$1) with application same database$1 and @rlad<="20020111" and "707"/$.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:35
L5	3925	(creat$3 generat$3 build$3) same (table$1) same (field$1 column$1) with table$1 same (user$1 client$1 near3 request$3)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:40
L6	1720	(creat$3 generat$3 build$3) with (table$1) same (field$1 column$1) with (user$1 client$1 near3 request$3)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:41
L7	620	(creat$3 generat$3 build$3) with (table$1) same (field$1 column$1) with (user$1 client$1 near3 request$3) and "707"/$.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:55
L8	175	(creat$3 generat$3 build$3) with (table$1) same (field$1 column$1) with (user$1 client$1 near3 request$3) and "707"/$.ccls. and @rlad<="20020111"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:43
L9	2	"6721742".pn.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 15:51
L10	1	"5448727".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:52
L11	1	"5684990".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:52

L12	1	"5870759".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:53
L13	1	"5870759".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:53
L14	1	"5966707".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:53
L15	1	"6012067".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:54
L16	1	"6167433".PN.	USPAT; USOCR	OR	OFF	2005/01/11 15:54
L17	39	(creat$3 generat$3 build$3) with (data adj structure$1) same (field$1 column$1) with (specif$5 designat$3 request$3) with (user$1 client$1 request$3) and "707"/$.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/11 16:01